

Cera Tec Premium Blue

Description

Micro ceramic solid lubricant suspension based on hexagonal boron nitride (BN) in selected base oils. The laminar graphite-similar structure reduces friction and wear and prevents direct metal-to-metal contact. The < 0.5 µm particle size guarantees optimum filter flow properties and protects against depositing of solid lubricant particles. Miscible with all commercially available motor oils and motor vehicle gear oils.

Properties

- reduces frictional losses
- suitable for diesel particulate filters
- miscible with all commercially available motor oils
- increases smooth operation
- highest thermal stability
- excellent high and low temperature behavior
- tested for turbochargers and catalytic converters
- stable under extreme pressures
- compatible with fine filters
- no deposits
- long engine service life
- chemically inert
- reduces fuel consumption

Technical data

Base	BN micro ceramic
Color / appearance	blue
Particle size	Majority < 0.5 µm
Ceramic particle size: Majority < 0.5 µm (TEST)	up to 1200 °C
Density at 20 °C	0,893 g/cm ³ DIN 51757
Viscosity at 20 °C	~250 mPas DIN 51398
Flash point	>100 °C DIN ISO 2592
Pour point	-20 °C DIN ISO 3016
Form	liquid
Odor	characteristic

Areas of application

For engines, manual transmissions, pumps and compressors. Excellent for car and commercial vehicle engines (gasoline and diesel). Suitable for toothed belts running in oil. Not suitable for use with wet clutches.

Comment

Not suitable for use with wet clutches!



Application

300 ml is sufficient for up to 5 liters of motor oil. Long-term effect up to 50,000 km. Shake well before use!

Available pack sizes

300 ml Bottle aluminum 2321
D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.